

KURO KAGE™ IRON

Mid Launch and Mid Spin

KURO KAGE SCI FLEX-S MITSUBISHI CHEMICAL

The KURO KAGE™ Iron shafts blend Low Resin Content (L.R.C.) Prepreg with a smooth bend profile to provide excellent versatility. These premium, cut-to-length, 42-inch iron shafts have a new cosmetic look, and are available in additional weights and flexes to meet the needs of players of all abilities.

SHAFT SPECIFICATIONS

Shaft Name	Flex	Length (in)	Weight (g)	Tip OD (in)	Tip // (in)	Butt OD (in)	Torque (deg)	Kick Point
KURO KAGE™ IRN 50	L	42	53	0.370	5.5	0.600	5.0	Mid
KURO KAGE™ IRN 60	A	42	60	0.370	5.5	0.590	5.0	Mid
KURO KAGE™ IRN 60	R	42	63	0.370	5.5	0.590	4.9	Mid
KURO KAGE™ IRN 60	S	42	66	0.370	5.5	0.600	4.9	Mid
KURO KAGE™ IRN 70	A	42	73	0.370	5.5	0.600	3.5	Mid
KURO KAGE™ IRN 70	R	42	75	0.370	5.5	0.600	3.5	Mid
KURO KAGE™ IRN 70	S	42	75	0.370	5.5	0.600	3.5	Mid
KURO KAGE™ IRN 80	R	42	80	0.370	5.5	0.600	4.1	Mid
KURO KAGE™ IRN 80	S	42	83	0.370	5.5	0.600	3.9	Mid
KURO KAGE™ IRN 90	R	42	90	0.370	5.5	0.600	3.5	Mid
KURO KAGE™ IRN 90	S	42	93	0.370	5.5	0.602	3.5	Mid
KURO KAGE™ IRN 100	X	42	100	0.370	4.0	0.602	2.6	Mid/High

INSTALLATION | TIP TRIMMING INSTRUCTIONS

2i	3i	4i	5i	6i	7i	8i	9i	PW
0"	0"	0.5"	1.0"	1.5"	2.0"	2.5"	3.0"	3.5"

¹ All shafts are designed to be butt trimmed to length.

² Shaft installation should only be completed by a qualified, trained club builder. To find an authorized Mitsubishi Chemical account in your area please visit our [dealer locator](#).