

KURO KAGE™ SILVER HYBRID

Mid Launch and Mid Spin



This stable and versatile profile is designed to match the performance characteristics of the high performing and versatile KURO KAGE™ Black woods with an updated cosmetic.

SHAFT SPECIFICATIONS

Shaft Name	Flex	Length (in)	Weight (g)	Tip OD (in)	Tip // (in)	Butt OD (in)	Torque (deg)	Kick Point
KURO KAGE™ Silver Hybrid 70	A	42.0	67	0.370	4.0	0.600	4.0	Mid
KURO KAGE™ Silver Hybrid 70	R	42.0	70	0.370	4.0	0.603	3.8	Mid
KURO KAGE™ Silver Hybrid 70	S	42.0	73	0.370	4.0	0.610	3.8	Mid
KURO KAGE™ Silver Hybrid 80	R	42.0	80	0.370	4.0	0.616	3.3	Mid
KURO KAGE™ Silver Hybrid 80	S	42.0	82	0.370	4.0	0.616	3.2	Mid
KURO KAGE™ Silver Hybrid 80	X	42.0	85	0.370	4.0	0.620	3.2	Mid/High

INSTALLATION | TIP TRIMMING INSTRUCTIONS

0"	0.5"	1.0"	1.5"	2.0"
----	------	------	------	------

¹All shafts are designed to be butt trimmed to length.

²Shaft installation should only be completed by a qualified, trained club builder. To find an authorized Mitsubishi Chemical account in your area please visit our [dealer locator](#).

Diamana™

TENSEI™

KURO KAGE™

FUBUKI™

BASSARA™

OT™

C6™