


# MMT™ IRONS (TAPER TIP)

## Mid Launch and Mid Spin

 MITSUBISHI CHEMICAL


ES

TYPE-304SS

Born from more than 30-years of composite shaft mastery, the new MMT Taper Iron utilizes a patent pending Metal Mesh Technology (MMT) to redefine the possibilities for feel and performance in a composite iron shaft. A unique metal mesh – made from individually braided strands of 304 Stainless Steel – is integrated into the shaft’s prepreg layers towards the tip. This improves density and stability, while also allowing for thinner overall composite wall construction. Together this yields a finely tuned, highly responsive shaft that still provides the consistent launch and spin control needed for effective iron play.

### SHAFT SPECIFICATIONS

Shaft Name	Flex	Length (in)	Weight (g)	Tip OD (in)	Tip // (in)	Butt OD (in)	Torque (deg)	Kick Point
MMT™ Taper Iron 55	A	39.5"	59	0.355	TAPER	0.594	3.5	MID
MMT™ Taper Iron 55	A	39"	59	0.355	TAPER	0.594	3.5	MID
MMT™ Taper Iron 55	A	38.5"	59	0.355	TAPER	0.594	3.5	MID
MMT™ Taper Iron 55	A	38"	59	0.355	TAPER	0.596	3.5	MID
MMT™ Taper Iron 55	A	37.5"	59	0.355	TAPER	0.596	3.5	MID
MMT™ Taper Iron 55	A	37"	59	0.355	TAPER	0.596	3.5	MID
MMT™ Taper Iron 55	A	36.5"	59	0.355	TAPER	0.6	3.5	MID
MMT™ Taper Iron 65	R	39.5"	63	0.355	TAPER	0.59	3.5	MID
MMT™ Taper Iron 65	R	39"	63	0.355	TAPER	0.59	3.5	MID
MMT™ Taper Iron 65	R	38.5"	63	0.355	TAPER	0.59	3.5	MID
MMT™ Taper Iron 65	R	38"	63	0.355	TAPER	0.59	3.5	MID
MMT™ Taper Iron 65	R	37.5"	63	0.355	TAPER	0.59	3.5	MID
MMT™ Taper Iron 65	R	37"	63	0.355	TAPER	0.592	3.5	MID
MMT™ Taper Iron 65	R	36.5"	63	0.355	TAPER	0.598	3.5	MID
MMT™ Taper Iron 75	S	40"	74	0.355	TAPER	0.606	3.7	MID
MMT™ Taper Iron 75	S	39.5"	74	0.355	TAPER	0.606	3.7	MID
MMT™ Taper Iron 75	S	39"	74	0.355	TAPER	0.606	3.7	MID
MMT™ Taper Iron 75	S	38.5"	74	0.355	TAPER	0.606	3.7	MID
MMT™ Taper Iron 75	S	38"	74	0.355	TAPER	0.606	3.7	MID
MMT™ Taper Iron 75	S	37.5"	74	0.355	TAPER	0.606	3.7	MID
MMT™ Taper Iron 75	S	37"	74	0.355	TAPER	0.606	3.7	MID
MMT™ Taper Iron 75	S	36.5"	74	0.355	TAPER	0.606	3.7	MID
MMT™ Taper Iron 75	S	36"	74	0.355	TAPER	0.606	3.7	MID
MMT™ Taper Iron 85	R	39"	84	0.355	TAPER	0.594	3.3	MID
MMT™ Taper Iron 85	R	38.5"	84	0.355	TAPER	0.594	3.3	MID
MMT™ Taper Iron 85	R	38"	84	0.355	TAPER	0.593	3.3	MID

# SHAFT SPECIFICATIONS

Shaft Name	Flex	Length (in)	Weight (g)	Tip OD (in)	Tip // (in)	Butt OD (in)	Torque (deg)	Kick Point
MMT™ Taper Iron 85	R	37.5"	84	0.355	TAPER	0.596	3.3	MID
MMT™ Taper Iron 85	R	37"	84	0.355	TAPER	0.596	3.3	MID
MMT™ Taper Iron 85	R	36.5"	84	0.355	TAPER	0.598	3.3	MID
MMT™ Taper Iron 85	R	36"	84	0.355	TAPER	0.598	3.3	MID
MMT™ Taper Iron 85	R	35.5"	84	0.355	TAPER	0.598	3.3	MID
MMT™ Taper Iron 85	S	39"	88	0.355	TAPER	0.602	3.2	MID
MMT™ Taper Iron 85	S	38.5"	88	0.355	TAPER	0.602	3.2	MID
MMT™ Taper Iron 85	S	38"	88	0.355	TAPER	0.602	3.2	MID
MMT™ Taper Iron 85	S	37.5"	88	0.355	TAPER	0.602	3.2	MID
MMT™ Taper Iron 85	S	37"	88	0.355	TAPER	0.602	3.2	MID
MMT™ Taper Iron 85	S	36.5"	88	0.355	TAPER	0.602	3.2	MID
MMT™ Taper Iron 85	S	36"	88	0.355	TAPER	0.602	3.2	MID
MMT™ Taper Iron 85	S	35.5"	88	0.355	TAPER	0.602	3.2	MID
MMT™ Taper Iron 105	S	39"	105	0.355	TAPER	0.598	2.8	MID
MMT™ Taper Iron 105	S	38.5"	105	0.355	TAPER	0.598	2.8	MID
MMT™ Taper Iron 105	S	38"	105	0.355	TAPER	0.598	2.8	MID
MMT™ Taper Iron 105	S	37.5"	105	0.355	TAPER	0.598	2.8	MID
MMT™ Taper Iron 105	S	37"	105	0.355	TAPER	0.598	2.8	MID
MMT™ Taper Iron 105	S	36.5"	105	0.355	TAPER	0.598	2.8	MID
MMT™ Taper Iron 105	S	36"	105	0.355	TAPER	0.598	2.8	MID
MMT™ Taper Iron 105	S	35.5"	105	0.355	TAPER	0.598	2.8	MID
MMT™ Taper Iron 105	TX	39"	113	0.355	TAPER	0.606	2.8	MID/HIGH
MMT™ Taper Iron 105	TX	38.5"	113	0.355	TAPER	0.606	2.8	MID/HIGH
MMT™ Taper Iron 105	TX	38"	113	0.355	TAPER	0.606	2.8	MID/HIGH
MMT™ Taper Iron 105	TX	37.5"	113	0.355	TAPER	0.606	2.8	MID/HIGH
MMT™ Taper Iron 105	TX	37"	113	0.355	TAPER	0.606	2.8	MID/HIGH
MMT™ Taper Iron 105	TX	36.5"	113	0.355	TAPER	0.606	2.8	MID/HIGH
MMT™ Taper Iron 105	TX	36"	113	0.355	TAPER	0.606	2.8	MID/HIGH
MMT™ Taper Iron 105	TX	35.5"	113	0.355	TAPER	0.606	2.8	MID/HIGH
MMT™ Taper Iron 125	TX	39"	125	0.355	TAPER	0.605	2.7	MID/HIGH
MMT™ Taper Iron 125	TX	38.5"	125	0.355	TAPER	0.605	2.7	MID/HIGH
MMT™ Taper Iron 125	TX	38"	125	0.355	TAPER	0.611	2.7	MID/HIGH
MMT™ Taper Iron 125	TX	37.5"	125	0.355	TAPER	0.609	2.7	MID/HIGH
MMT™ Taper Iron 125	TX	37"	125	0.355	TAPER	0.609	2.7	MID/HIGH
MMT™ Taper Iron 125	TX	36.5"	125	0.355	TAPER	0.608	2.7	MID/HIGH
MMT™ Taper Iron 125	TX	36"	125	0.355	TAPER	0.608	2.7	MID/HIGH
MMT™ Taper Iron 125	TX	35.5"	125	0.355	TAPER	0.606	2.7	MID/HIGH

Diamana™

TENSEI™

KURO KAGE™

FUBUKI™

BASSARA™

OT™

MMT™

C6™

<sup>1</sup> All shafts are designed to be butt trimmed to length.

<sup>2</sup> Shaft installation should only be completed by a qualified, trained club builder. To find an authorized Mitsubishi Chemical account in your area please visit our dealer locator.