

TENSEI™ AV RAW BLUE

MID LAUNCH, MID/LOWSPIN



TENSEI™ AV RAW Blue blends modern performance with a classic, smooth bend profile. The RAW finish reveals the Aluminum Vapor (AV) Coated Weave in the butt section, a visible cue of the added stability this unique weave provides. Power transfers straight from the hands through the ball for a consistent, mid-launching flight. The 55g option includes our Straight Flight Weighting (SFW) system which makes it easier to turn the club over through impact, reducing the tendency to fade the ball or even promoting a slight draw. TENSEI™ AV RAW Blue is best for players who want a mid-launching ball flight with a feeling of greater stability and control throughout the swing.

Technologies: Low Resin Content (L.R.C.) Prepreg, Aluminum Vapor (AV) Coated Weave, Ultra-Lightweight Materials, Straight Flight Weighting (SFW) System

SHAFT SPECIFICATIONS

Shaft Name	Flex	Length (in)	Weight (g)	Tip OD (in)	Tip (in)	Butt OD(in)	Torque (deg)	Kick Pt.
TENSEI™ AV RAW Blue 55	R2	46	55	0.335	3	0.600	5.5	MID
TENSEI™ AV RAW Blue 55	R	46	57	0.335	3	0.600	5.4	MID
TENSEI™ AV RAW Blue 55	S	46	58	0.335	3	0.598	4.9	MID
TENSEI™ AV RAW Blue 55	X	46	62	0.335	3	0.600	4.6	MID
TENSEI™ AV RAW Blue 65	R	46	65	0.335	3	0.597	4.4	MID
TENSEI™ AV RAW Blue 65	S	46	67	0.335	3	0.598	3.9	MID
TENSEI™ AV RAW Blue 65	X	46	68	0.335	3	0.598	3.4	MID
TENSEI™ AV RAW Blue 65	TX	46	69	0.335	3	0.638	3.6	MID
TENSEI™ AV RAW Blue 75	R	46	74	0.335	3	0.598	4.1	MID
TENSEI™ AV RAW Blue 75	S	46	77	0.335	3	0.600	3.9	MID
TENSEI™ AV RAW Blue 75	X	46	78	0.335	3	0.600	3.4	MID
TENSEI™ AV RAW Blue 75	TX	46	79	0.335	3	0.641	3.2	MID
TENSEI™ AV RAW Blue 85	TX	46	86	0.335	3	0.634	2.6	MID

FITTING GUIDE

Driver Speed MPH/YDS	80/210	81-90/210-239	91-105/240-259	106/260
TENSEI™ AV RAW Blue 55 w/ SFW	R2	R	S	X/TX
TENSEI™ AV RAW Blue 65		R	S	X/TX
TENSEI™ AV RAW Blue 75		R	S	X/TX
TENSEI™ AV RAW Blue 85				TX

INSTALLATION | TIP TRIMMING INSTRUCTIONS

Driver	3 Wood	5 Wood	7 Wood	9 Wood
0"	0.5"	0.75"	1.0"	1.0"

¹ All shafts are designed to be butt trimmed to length.

² Shaft installation should only be completed by a qualified, trained club builder. To find an authorized Mitsubishi Chemical account in your area please visit our dealer locator.