

# TENSEI™ AV RAW ORANGE

MID LAUNCH, LOW SPIN (TX-FLEXES LOW LAUNCH, LOW SPIN)



TENSEI™ AV RAW Series refines the player-revered performance of TENSEI™ AV Blue and establishes a full range of fitting options. All three feature a RAW finish that reveals the Aluminum Vapor (AV) Coated Weave in the butt section, a visible cue of the added stability this unique weave provides.

TENSEI™ AV RAW Orange is a Counter-Balanced shaft that shifts the balance point towards the hands, giving players the opportunity to make specific performance adjustments by altering shaft length or adding weight to the clubhead. The RAW finish reveals the Aluminum Vapor (AV) Coated Weave in the butt section, a visible cue of the added stability this unique weave provides. Power transfers straight from the hands through the ball for consistent, mid-launching flight.

Technologies: Low Resin Content (L.R.C.) Prepreg, Aluminum Vapor (AV) Coated Weave, Ultra-Lightweight Materials

## SHAFT SPECIFICATIONS

Shaft Name	Flex	Length (in)	Weight (g)	Tip OD (in)	Tip (in)	Butt OD(in)	Torque (deg)	Kick Pt.
TENSEI™ AV RAW Orange 55	R	46	57	0.335	3	0.608	6.0	MID
TENSEI™ AV RAW Orange 55	S	46	60	0.335	3	0.610	5.9	MID
TENSEI™ AV RAW Orange 55	X	46	62	0.335	3	0.612	5.8	MID
TENSEI™ AV RAW Orange 65	R	46	66	0.335	3	0.616	4.5	MID
TENSEI™ AV RAW Orange 65	S	46	69	0.335	3	0.618	4.4	MID
TENSEI™ AV RAW Orange 65	X	46	70	0.335	3	0.620	4.3	MID
TENSEI™ AV RAW Orange 65	TX	46	70	0.335	3	0.610	3.5	HIGH
TENSEI™ AV RAW Orange 75	R	46	75	0.335	3	0.616	3.9	MID
TENSEI™ AV RAW Orange 75	S	46	77	0.335	3	0.618	3.8	MID
TENSEI™ AV RAW Orange 75	X	46	78	0.335	3	0.620	3.7	MID
TENSEI™ AV RAW Orange 75	TX	46	78	0.335	3	0.612	3.0	HIGH
TENSEI™ AV RAW Orange 85	TX	46	82	0.335	3	0.598	2.8	HIGH

## FITTING GUIDE

Driver Speed MPH/YDS	80/210	81-90/210-239	91-105/240-259	106/260
TENSEI™ AV RAW Orange 55		R	S	X/TX
TENSEI™ AV RAW Orange 65		R	S	X/TX
TENSEI™ AV RAW Orange 75		R	S	X/TX
TENSEI™ AV RAW Orange 85				TX

## INSTALLATION [TIP TRIMMING INSTRUCTIONS]

Driver	3 Wood	5 Wood	7 Wood	9 Wood
0"	0.5"	0.75"	1.0"	1.0"

<sup>1</sup> All shafts are designed to be butt trimmed to length.

<sup>2</sup> Shaft installation should only be completed by a qualified, trained club builder. To find an authorized Mitsubishi Chemical account in your area please visit our dealer locator.