

TENSEI™ 1K PRO WHITE

LOW LAUNCH, LOW SPIN



TENSEI™ 1K Pro White is built for the player who seeks perfection. Created using extraordinary 1K Fiber that is 3x thinner than Carbon Kevlar for a tighter, more consistent weave, this super premium fiber produces an amazing "1K feel" by transmitting more of the high frequency vibrations needed to feel the true quality of impact. Our breakthrough, dual-phase Xlink Tech™ Resin System is used through the full length of the shaft for a carbon-rich structure that maximizes feel while increasing the overall strength of the shaft. Golfers can expect maximum control and reduced torque from TENSEI™ 1K Pro White through the use of 46-ton carbon fiber. Boron is used in the tip to cap off this exceptional design. Available from 50R to 80TX, TENSEI™ 1K Pro White gives a wide range of players the opportunity to play the best TENSEI™ we've ever made.

SHAFT SPECIFICATIONS

Shaft Name	Flex	Length (in)	Weight (g)	Tip OD (in)	Tip (in)	Butt OD(in)	Torque (deg)	Kick Pt.
TENSEI™ 1K Pro White 50	R	46"	54	0.335	3	0.598	4.6	HIGH
TENSEI™ 1K Pro White 50	S	46"	56	0.335	3	0.601	4.5	HIGH
TENSEI™ 1K Pro White 50	X	46"	59	0.335	3	0.601	4.4	HIGH
TENSEI™ 1K Pro White 50	TX	46"	61	0.335	3	0.601	4.4	HIGH
TENSEI™ 1K Pro White 60	R	46"	60	0.335	3	0.596	3.8	HIGH
TENSEI™ 1K Pro White 60	S	46"	62	0.335	3	0.602	3.8	HIGH
TENSEI™ 1K Pro White 60	X	46"	65	0.335	3	0.603	3.8	HIGH
TENSEI™ 1K Pro White 60	TX	46"	67	0.335	3	0.603	3.8	HIGH
TENSEI™ 1K Pro White 70	S	46"	71	0.335	3	0.604	3.4	HIGH
TENSEI™ 1K Pro White 70	X	46"	75	0.335	3	0.607	3.3	HIGH
TENSEI™ 1K Pro White 70	TX	46"	76	0.335	3	0.607	3.2	HIGH
TENSEI™ 1K Pro White 80	S	46"	81	0.335	3	0.626	2.8	HIGH
TENSEI™ 1K Pro White 80	X	46"	81	0.335	3	0.626	2.8	HIGH
TENSEI™ 1K Pro White 80	TX	46"	86	0.335	3	0.626	2.7	HIGH

FITTING GUIDE

Driver Speed MPH/YDS	<80/<210	81-90/210-230	91-105/241-259	>106/>260
TENSEI™ 1K Pro White 50		R	S	TX
TENSEI™ 1K Pro White 60		R	S	TX
TENSEI™ 1K Pro White 70			S	TX
TENSEI™ 1K Pro White 80				TX

INSTALLATION | TIP TRIMMING INSTRUCTIONS

Driver	3 Wood	5 Wood	7 Wood	9 Wood
0"	0.5"	0.75"	1.0"	1.0"

¹ All shafts are designed to be butt trimmed to length.

² Shaft installation should only be completed by a qualified, trained club builder. To find an authorized Mitsubishi Chemical account in your area please visit our dealer locator.