

# Diamana™ B-SERIES

## Mid Launch and Mid to Low Spin



The B-series profile represents the next evolution in MCC's signature "smooth" bend profile offering "balanced" stiffness on both ends of the shaft with a slightly "stiffer" mid-section. The profile was first made popular in 2005 with the debut of the initial Diamana™ S-Series (Blue Board).

Its sheer power is a tribute to it being made with strong "pitch" carbon fiber. Building on the success of our signature smooth profile embodied in our Diamana™ Kai'li, it maximizes energy transfer by stabilizing the butt section.

### SHAFT SPECIFICATIONS

| Shaft Name           | Flex | Length (in) | Weight (g) | Tip OD (in) | Tip // (in) | Butt OD (in) | Torque (deg) | Kick Point |
|----------------------|------|-------------|------------|-------------|-------------|--------------|--------------|------------|
| Diamana™ B-Series 50 | R    | 46.0        | 55         | 0.335       | 3.0         | 0.608        | 4.3          | Mid        |
| Diamana™ B-Series 50 | S    | 46.0        | 57         | 0.335       | 3.0         | 0.612        | 4.2          | Mid/High   |
| Diamana™ B-Series 50 | X    | 46.0        | 60         | 0.335       | 3.0         | 0.616        | 4.2          | Mid/High   |
| Diamana™ B-Series 60 | R    | 46.0        | 62         | 0.335       | 3.0         | 0.602        | 3.8          | Mid/High   |
| Diamana™ B-Series 60 | S    | 46.0        | 64         | 0.335       | 3.0         | 0.606        | 3.6          | Mid/High   |
| Diamana™ B-Series 60 | X    | 46.0        | 67         | 0.335       | 3.0         | 0.610        | 3.5          | Mid/High   |
| Diamana™ B-Series 70 | S    | 46.0        | 74         | 0.335       | 3.0         | 0.630        | 3.0          | Mid/High   |
| Diamana™ B-Series 70 | X    | 46.0        | 77         | 0.335       | 3.0         | 0.635        | 2.9          | Mid/High   |
| Diamana™ B-Series 80 | S    | 46.0        | 84         | 0.335       | 3.0         | 0.630        | 2.8          | Mid/High   |
| Diamana™ B-Series 80 | X    | 46.0        | 87         | 0.335       | 3.0         | 0.635        | 2.8          | Mid/High   |

### INSTALLATION | TIP TRIMMING INSTRUCTIONS

| Driver | 3 Wood | 5 Wood | 7 Wood | 9 Wood |
|--------|--------|--------|--------|--------|
| 0"     | 0.5"   | 0.75"  | 1.0"   | 1.0"   |

<sup>1</sup> All shafts are designed to be butt trimmed to length.

<sup>2</sup> Shaft installation should only be completed by a qualified, trained club builder. To find an authorized Mitsubishi Chemical account in your area please visit our [dealer locator](#).