

KURO KAGE™ SILVER TiNi

Mid Launch and Mid to Low Spin

KURO KAGE

EOS FLEX-S

MITSUBISHI CHEMICAL

The KURO KAGE™ Silver TiNi Series features a tip-stiff bend profile, offering more feel in the hands, with extreme control. Our TiNi Wire and Low Resin Content (L.R.C.) Prepreg is positioned in the lower third of the shaft for increased stability and feel at impact.

SHAFT SPECIFICATIONS

Shaft Name	Flex	Length (in)	Weight (g)	Tip OD (in)	Tip // (in)	Butt OD (in)	Torque (deg)	Kick Point
KURO KAGE™ Silver TiNi 50	R	46.0	57	0.335	3.0	0.614	5.2	Mid
KURO KAGE™ Silver TiNi 50	S	46.0	59	0.335	3.0	0.616	5.1	Mid
KURO KAGE™ Silver TiNi 50	X	46.0	60	0.335	3.0	0.618	4.8	Mid/High
KURO KAGE™ Silver TiNi 60	R	46.0	65	0.335	3.0	0.614	4.6	Mid
KURO KAGE™ Silver TiNi 60	S	46.0	67	0.335	3.0	0.618	4.4	Mid
KURO KAGE™ Silver TiNi 60	X	46.0	69	0.335	3.0	0.620	3.3	Mid/High
KURO KAGE™ Silver TiNi 70	S	46.0	76	0.335	3.0	0.618	4.1	Mid/High
KURO KAGE™ Silver TiNi 70	X	46.0	77	0.335	3.0	0.620	3.0	Mid/High
KURO KAGE™ Silver TiNi 80	X	46.0	86	0.335	3.0	0.620	2.8	Mid/High
KURO KAGE™ Silver TiNi 90	X	46.0	97	0.335	3.0	0.630	2.6	Mid/High

INSTALLATION | TIP TRIMMING INSTRUCTIONS

Driver	3 Wood	5 Wood	7 Wood	9 Wood
0"	0.5"	0.75"	1.0"	1.0"

¹ All shafts are designed to be butt trimmed to length.

² Shaft installation should only be completed by a qualified, trained club builder. To find an authorized Mitsubishi Chemical account in your area please visit our **dealer locator**.

Diamana™

TENSEI™

KURO KAGE™

FUBUKI™

BASSARA™

OT™

C6™