

# KURO KAGE™ XD

## Low Launch and Low Spin



The KURO KAGE™ XD utilizes premium 40-Ton and 46-Ton carbon fiber as well as an ultra-long application of the TiNi Wire prepreg in the tip section. We've taken the TiNi Wire and increased its length by 1.5 times along the outer layer. The design lowers launch and spin, and delivers a new level of stability and control.

The KURO KAGE™ XD comes in a premium ion plated finish.

### SHAFT SPECIFICATIONS

Shaft Name	Flex	Length (in)	Weight (g)	Tip OD (in)	Tip // (in)	Butt OD (in)	Torque (deg)	Kick Point
KURO KAGE™ XD 50	R	46	54	0.335	3.0	0.600	5.7	High
KURO KAGE™ XD 50	S	46	58	0.335	3.0	0.604	5.5	High
KURO KAGE™ XD 50	X	46	62	0.335	3.0	0.610	5.5	High
KURO KAGE™ XD 60	S	46	65	0.335	3.0	0.602	3.5	High
KURO KAGE™ XD 60	X	46	67	0.335	3.0	0.604	3.4	High
KURO KAGE™ XD 60	TX	46	68	0.335	3.0	0.606	3.4	High
KURO KAGE™ XD 70	S	46	72	0.335	3.0	0.604	3.0	High
KURO KAGE™ XD 70	X	46	74	0.335	3.0	0.606	2.9	High
KURO KAGE™ XD 70	TX	46	75	0.335	3.0	0.608	2.9	High
KURO KAGE™ XD 80	S	46	82	0.335	3.0	0.606	3.0	High
KURO KAGE™ XD 80	X	46	84	0.335	3.0	0.608	2.9	High
KURO KAGE™ XD 80	TX	46	85	0.335	3.0	0.610	2.9	High

### INSTALLATION | TIP TRIMMING INSTRUCTIONS

Driver	3 Wood	5 Wood	7 Wood	9 Wood
0"	0.5"	0.75"	1.0"	1.0"

<sup>1</sup> All shafts are designed to be butt trimmed to length.

<sup>2</sup> Shaft installation should only be completed by a qualified, trained club builder. To find an authorized Mitsubishi Chemical account in your area please visit our [dealer locator](#).