

TENSEI™ AV HYBRID/IRON

Mid Launch and Mid Spin



The TENSEI™ AV Hybrid/Iron incorporates Aluminum Vapor(AV) Coated Fiber that adds additional stability to achieve our desired profile and stiffness targets. The AV weave on this newer TENSEI™ Hybrid/Iron Series is tighter and thinner than the original Carbon Fiber/Kevlar® (CK) weave. The result is a versatile profile, with reduced overall weight and increased stiffness in the butt section to help prevent shaft ovaling and improve energy transfer.

TENSEI™ AV Hybrid/Iron is a cut-to-length, 42-inch hybrid/iron shaft that is available in a range of weights and flexes to meet the performance needs of a wide range of players.

SHAFT SPECIFICATIONS

Shaft Name	Flex	Length (in)	Weight (g)	Tip OD (in)	Tip // (in)	Butt OD (in)	Torque (deg)	Kick Point
TENSEI™ AV Hybrid/Iron 55	A	42.0	61	0.370	5.5	0.590	4.8	Mid
TENSEI™ AV Hybrid/Iron 60	R	42.0	64	0.370	5.5	0.594	4.7	Mid
TENSEI™ AV Hybrid/Iron 65	S	42.0	66	0.370	5.5	0.598	4.7	Mid
TENSEI™ AV Hybrid/Iron 60	A	42.0	66	0.370	5.5	0.596	4.1	Mid
TENSEI™ AV Hybrid/Iron 65	R	42.0	69	0.370	5.5	0.602	4.1	Mid
TENSEI™ AV Hybrid/Iron 70	S	42.0	77	0.370	5.5	0.600	3.4	Mid
TENSEI™ AV Hybrid/Iron 75	X	42.0	82	0.370	5.5	0.606	3.4	Mid

INSTALLATION | TIP TRIMMING INSTRUCTIONS

2i	3i	4i	5i	6i	7i	8i	9i	PW
0"	0"	0.5"	1.0"	1.5"	2.0"	2.5"	3.0"	3.5"

¹ All shafts are designed to be butt trimmed to length.

² Shaft installation should only be completed by a qualified, trained club builder. To find an authorized Mitsubishi Chemical account in your area please visit our [dealer locator](#).

Diamana™

TENSEI™

KURO KAGE™

FUBUKI™

BASSARA™

OT™

C6™